

## **TECHNICAL DATA SHEET**

## PRODUCT DISCRPTION

EVA foam backing, a coating on the single side or both side with strong solvent acrylic adhesive.



| Discription                     | Single Side Foam Tape | Double Side Foam Tape | Test Condition     |
|---------------------------------|-----------------------|-----------------------|--------------------|
| Thickness (mm)                  | 1±0.005/3±0.005       | 1±0.005/3±0.005       | -                  |
| Carrier                         | EVA                   | EVA                   | -                  |
| Color                           | White / Black         | White / Black         | -                  |
| Initial Tack14# Steel Ball (mm) | ≥ 100                 | ≥ 100                 | GB / T 4852 - 2002 |
| Peeling Strength (N/25mm)       | ≥ 15                  | ≥ 15                  | GB/T 2792 - 1998   |
| Holding Power 25 c° (hr)        | ≥ 12                  | ≥ 12                  | GB / T 4851 - 1998 |

## **FEATURES:**

Strong adhesive / Good mitigating vibratility / Strong crack resistance / High temperature - resistance / High seal property.

## **IDEAL APPLICATION**

Applicable for permanent fixing.

For Irregular surface.

For mounting decorative objects in cars, machines or houses.

**NOTE:** Information in the above sheet is only for reference, it should be considered as representative or typical parameters and should not be taken as the exact values of every single product. Customers have the obligation to check whether the product is suitable for their own applications.