

TECHNICAL DATA SHEET

PRODUCT DISCRPTION

Fiba Joint Tape self-adhesive, drywall joint tape saves on application and dry-time by eliminating the bedding coat required for paper tape installation. Fiberglass mesh is thin and easy to conceal while providing increased crack resistance.

Product Name	Test Standard	Test Environment	Specifications
Fiberglass self Adhesive Tape Jumbo Roll	GC561.2 - 2003	Temperature: 23° C Humidity: 65 %	3mm x 3mm / 60g
Warp Tex : 33 Tex		Weft Tex : 33 Tex	

Test Item	Unit	Standard Values	Measured Values	Test Result
Width	cm	120 cm	120 cm	Up to standard
Weight	g/m ²	60 ± 5 %	61	Up to standard
Warp density	Yarn / 10cm	32 Yarn	32 Yarn	Up to standard
Weft density	Yarn / 10cm	32 Yarn	32 Yarn	Up to standard
Warp tensile strength	N / 50 mm	780N	800N	Up to standard
Weft tensile strength	N / 50 mm	780N	820N	Up to standard
Content of Resin %	g/m ²	25%	26%	Up to standard
Alkali Resistance	%	≥50 %	50%	Up to standard

IDEAL APPLICATION

Drywall joints / Drywall finishing / Crack repair

NOTE : *Information in the above sheet is only for reference, it should be considered as representative or typical parameters and should not be taken as the exact values of every single product. Customers have the obligation to check whether the product is suitable for their own applications.*